



TYRE CATALOGUE



KING OF TYRES

ATTITUDE IS THE PRODUCT OF BELIEF

OTR

POWERED BY



WWW.ETD.NL



THE POWER OF LEAO TYRES

As the King of Tyres, LEAO offers you the perfect tyres to rule any terrain. Whether you are looking for TBR, AGR or OTR tyres, LEAO tyres guarantee economical prices, excellent quality and 100% reliability.

The lion in the logo reflects exactly what it is all about: the excellent, nearly “royal” capabilities provided by LEAO tyres. LEAO tyres match the requirements and desires of many different users perfectly and they have proven their value on all types of surfaces and under all weather conditions.

The broad range of modern LEAO patterns is continuously adapted to the demands of the European market. This makes LEAO a brand with state-of-the-art patterns ready to attack the terrain.

If you are looking for an excellent value-for-money option, LEAO tyres is the brand to choose as nothing beats a lion!

More information: www.leao-tyres.com



PATTERN OVERVIEW



LBO1N E3/L3/G3 **

PAGE 6



LBO6S E3 **

PAGE 6



LBO2SD L5T **

PAGE 7



LBO3SD L5R **

PAGE 7



LMS401 E4 **

PAGE 8



DM992 ***

PAGE 8



D990 **

PAGE 9



LBO3S E4 **

PAGE 9



LBO2S E4 **

PAGE 10

TABLE OF CONTENTS

SIZE	PATTERN	LOAD/SPEED	PAGE
16.00R20	D990 **	174/171F	9
17.5R25	LB01N E3/L3/G3 **	167B/182A2	6
17.5R25	LB03SD L5R **	167B/182A2	7
20.5R25	LB01N E3/L3/G3 **	177B/193A2	6
20.5R25	LB02SD L5T **	177B/193A2	7
20.5R25	LB03SD L5R **	177B/193A2	7
23.5R25	LB01N E3/L3/G3 **	185B/201A2	6
23.5R25	LB02SD L5T **	185B/201A2	7
23.5R25	LB03SD L5R **	185B/201A2	7
26.5R25	LB01N E3/L3/G3 **	193B/209A2	6
26.5R25	LB02SD L5T **	193B/209A2	7
26.5R25	LB03SD L5R **	193B/209A2	7
29.5R25	LB01N E3/L3/G3 **	200B/216A2	6
29.5R25	LB02SD L5T **	200B/216A2	7
29.5R25	LB03SD L5R **	200B/216A2	7
29.5R25	LMS401 E4 **	200B/216A2	8
14.00R25	DM992 ***	169B/188A2	8
16.00R25	LB03S E4 **	177B/195A2	9
18.00R25	LB03S E4 **	185B/204A2	9
750/65R25	LB06S E3 **	190B	6
18.00R33	LB02S E4 **	191B/209A2	10

Disclaimer

The information in this brochure is based on our manufacturer's specifications. This information is for general information purposes only. Any reliance you place on the information shown in this brochure is therefore strictly at your own risk. European Tyre Distributors is not liable for any loss or damage arising from the use of this brochure.

LB01N E3/L3/G3 **

LOADER

- GREAT FLOTATION
- EXCEPTIONAL TRACTION AND MANEUVERABILITY
- EXCELLENT STABILITY AND COMFORT



SIZE	PR	CODE	LOAD (KG) / SPEED (KM/H)		RIM	10 KM/H		50 KM/H		OVERALL DIAMETER (MM)	STATIC LOAD RADIUS (MM)	ROLLING CIRCUM-FERENCE	WIDTH (MM)	TREAD DEPTH (MM)
			TRANSP 50 KM/H SPEED SYMBOL B	LOADING 10 KM/H SPEED SYMBOL A2		LOAD (KG)	PRESSURE (KPA)	LOAD (KG)	PRESSURE (KPA)					
17.5R25	**	E3/L3/G3	167	182	14.00/1.5	8500	575	5450	450	1348	599	4057	445	27
20.5R25	**	E3/L3/G3	177	193	17.00/2.0	11500	575	7300	450	1492	664	4502	520	30
23.5R25	**	E3/L3/G3	185	201	19.50/2.5	14500	575	9250	450	1873	720	4480	597	33
26.5R25	**	E3/L3/G3	193	209	22.00/3.0	18500	575	11500	450	1617	779	5277	673	36
29.5R25	**	E3/L3/G3	200	216	25.00/3.5	22400	575	14000	450	1750	843	5713	750	39

LB06S E3 **

DUMP TRUCK

- GREAT TRACTION AND WEAR RESISTANCE
- EXCELLENT TEAR RESISTANCE
- COMFORTABLE ON- AND OFF-ROAD



SIZE	PR	CODE	LOAD (KG) / SPEED (KM/H)		RIM	10 KM/H		50 KM/H		OVERALL DIAMETER (MM)	STATIC LOAD RADIUS (MM)	ROLLING CIRCUM-FERENCE	WIDTH (MM)	TREAD DEPTH (MM)
			TRANSP 50 KM/H SPEED SYMBOL B	LOADING 10 KM/H SPEED SYMBOL A2		LOAD (KG)	PRESSURE (KPA)	LOAD (KG)	PRESSURE (KPA)					
750/65R25	**	E3	190	-	24.00/3.0	-	-	10600	425	1610	720	4880	754	45

LB02SD L5T **

LOADER

- EXCEPTIONAL TRACTION
- EXTRA DEEP TREAD PATTERN ENSURES OUTSTANDING LONG PRODUCT LIFE
- SQUARE TREAD GIVES GOOD STABILITY WHILST DRIVING



SIZE	PR	CODE	LOAD (KG) / SPEED (KM/H)		RIM	10 KM/H		50 KM/H		OVERALL DIAMETER (MM)	STATIC LOAD RADIUS (MM)	ROLLING CIRCUM-FERENCE	WIDTH (MM)	TREAD DEPTH (MM)
			TRANSP 50 KM/H SPEED SYMBOL B	LOADING 10 KM/H SPEED SYMBOL A2		LOAD (KG)	PRESSURE (KPA)	LOAD (KG)	PRESSURE (KPA)					
20.5R25	**	L5T	177	193	17.00/2.0	7300	450	11500	575	1548	697	4721	520	71
23.5R25	**	L5T	185	201	19.50/2.5	9250	450	14500	575	1673	753	5103	597	77.5
26.5R25	**	L5T	193	209	22.00/3.0	11500	450	18500	575	1798	809	5484	673	86.5
29.5R25	**	L5T	200	216	25.00/3.5	14000	450	22400	575	1921	864	5859	750	94

LB03SD L5R **

LOADER

- EXCELLENT COMBINATION OF ADHESION AND TRACTION
- EXCEPTIONALLY ROBUST IN TOUGH CONDITIONS
- ROBUST REINFORCED SHOULDERS WITH A PROTECTION BAND



SIZE	PR	CODE	LOAD (KG) / SPEED (KM/H)		RIM	10 KM/H		50 KM/H		OVERALL DIAMETER (MM)	STATIC LOAD RADIUS (MM)	ROLLING CIRCUM-FERENCE	WIDTH (MM)	TREAD DEPTH (MM)
			TRANSP 50 KM/H SPEED SYMBOL B	LOADING 10 KM/H SPEED SYMBOL A2		LOAD (KG)	PRESSURE (KPA)	LOAD (KG)	PRESSURE (KPA)					
17.5R25	**	L5R	167	182	14.00/1.5	5450	450	8500	575	1399	630	4267	445	64
20.5R25	**	L5R	177	193	17.00/2.0	7300	450	11500	575	1548	697	4721	520	71
23.5R25	**	L5R	185	201	19.50/2.5	9250	450	14500	575	1673	753	5103	597	77.5
26.5R25	**	L5R	193	209	22.00/3.0	11500	450	18500	575	1798	809	5484	673	86.5
29.5R25	**	L5R	200	216	25.00/3.5	14000	450	22400	575	1921	864	5859	750	94

LMS401 E4 **

UNDERGROUND WORK

- SUITABLE FOR LOADERS OPERATING UNDER TOUGH CONDITIONS
- ENHANCED SHOULDER WEAR AND CUT RESISTANCE
- ENHANCED TREAD WEAR RESISTANCE



SIZE	PR	CODE	LOAD (KG) / SPEED (KM/H)		RIM	10 KM/H		50 KM/H		OVERALL DIAMETER (MM)	STATIC LOAD RADIUS (MM)	ROLLING CIRCUM-FERENCE	WIDTH (MM)	TREAD DEPTH (MM)
			TRANSP 50 KM/H SPEED SYMBOL B	LOADING 10 KM/H SPEED SYMBOL A2		LOAD (KG)	PRESSURE (KPA)	LOAD (KG)	PRESSURE (KPA)					
29.5R25	**	E4	200	216	25.00/3.5	14000	450	22400	575	1921	864	5859	750	61

DM992 ***

DUMP TRUCK

- LONG PRODUCT LIFE
- EXCELLENT ADHESION AND TRACTION IN TOUGH CONDITIONS
- EXCELLENT TEAR RESISTANCE



SIZE	PR	CODE	LOAD (KG) / SPEED (KM/H)		RIM	10 KM/H		50 KM/H		OVERALL DIAMETER (MM)	STATIC LOAD RADIUS (MM)	ROLLING CIRCUM-FERENCE	WIDTH (MM)	TREAD DEPTH (MM)
			TRANSP 50 KM/H SPEED SYMBOL B	LOADING 10 KM/H SPEED SYMBOL A2		LOAD (KG)	PRESSURE (KPA)	LOAD (KG)	PRESSURE (KPA)					
14.00R25	***	-	169	188	10.00	5800	700	10000	950	1370	617	4179	375	24

D990 **

ON & OFF-ROAD

- LONG PRODUCT LIFE
- GOOD TRACTION
- EXCELLENT WEAR AND TEAR RESISTANCE



SIZE	PR	CODE	LOAD INDEX	SPEED INDEX	RIM	10 KM/H		50 KM/H		OVERALL DIAMETER (MM)	STATIC LOAD RADIUS (MM)	ROLLING CIRCUM-FERENCE	WIDTH (MM)	TREAD DEPTH (MM)
						LOAD (KG)	PRESSURE (KPA)	LOAD (KG)	PRESSURE (KPA)					
16.00R20	**	-	174	171F	11.25	-	-	-	-	1318	593	4020	433	20.5

LB03S E4 **

DUMP TRUCK

- WIDE CONTACT AREA WITH GROUND PROVIDES STRONG GRIP
- HIGH SAFETY
- LOW ROLLING NOISE



SIZE	PR	CODE	LOAD (KG) / SPEED (KM/H)		RIM	10 KM/H		50 KM/H		OVERALL DIAMETER (MM)	STATIC LOAD RADIUS (MM)	ROLLING CIRCUM-FERENCE	WIDTH (MM)	TREAD DEPTH (MM)
			TRANSP 50 KM/H SPEED SYMBOL B	LOADING 10 KM/H SPEED SYMBOL A2		LOAD (KG)	PRESSURE (KPA)	LOAD (KG)	PRESSURE (KPA)					
16.00R25	**	E4	177	195	11.25/2.0	7300	650	12150	800	1548	686	4651	432	42
18.00R25	**	E4	185	204	13.00/2.5	9250	650	16000	800	1673	744	5045	498	46

LBO2S E4 **

EARTHMOVER

- EXCEPTIONAL TRACTION AND MANEUVERABILITY
- GOOD FLOTATION
- EXCELLENT STABILITY AND COMFORT



SIZE	PR	CODE	LOAD (KG) / SPEED (KM/H)		RIM	10 KM/H		50 KM/H		OVERALL DIAMETER (MM)	STATIC LOAD RADIUS (MM)	ROLLING CIRCUM-FERENCE	WIDTH (MM)	TREAD DEPTH (MM)
			TRANSP 50 KM/H SPEED SYMBOL B	LOADING 10 KM/H SPEED SYMBOL A2		LOAD (KG)	PRESSURE (KPA)	LOAD (KG)	PRESSURE (KPA)					
18.00R33	**	E4	191	209	13.00/2.5	10900	650	18500	800	1877	835	5661	498	53



LEAO



**IT'S
GOOD
TO BE
THE
KING!**

KING OF TYRES

ATTITUDE IS THE PRODUCT OF BELIEF



ETD - YOUR WHOLESALE FOR THE COMPLETE PACKAGE

European Tyre Distributors B.V. (ETD) specializes in the import of Asian tyres for the European market, with the brands LEAO and Security as its flagships. Due to the well-established partnerships with top Asian manufacturers ETD can guarantee the quick supply of high quality products straight from Asia or from ETD's 20.000 m² of warehouses near Rotterdam, the Netherlands.

While ETD's core business is tyres, in all different ranges and sizes, they also offer a good selection of accompanying products such as tubes and wheels. ETD therefore is a reliable partner in TBR, AGR, OTR, PCR but also in niche markets such as trailer, industrial and crossply tyres.

Next to their substantial range, ETD is also known for its great service. With forty years of experience they are able to provide the best advice tailored to the customers' specific requests.

Overall, European Tyre Distributors stands for a large range of quality tyres, competitive prices and a level of service that surpasses international competition.

CONTACT

European Tyre Distributors B.V.
P.O. Box 5722, 3291 AA Strijen, The Netherlands
Industriestraat 12, 3291 CC Strijen, The Netherlands

Tel: +31 (0)78 629 1210
Email: sales@etd.nl
www.etd.nl